

UNGER

Quality Tools for Smart Cleaning

**HYDRO
POWER**® **RO S**
SYSTEM



MADE IN
GERMANY

**HYDRO POWER® RO S
PURE WATER FOR EVERYONE!**

NEW!



Quality Tools for Smart Cleaning

YOUR ECONOMICAL SOLUTION FOR CLEANING WITH PURE WATER IN HARD WATER AREAS

With the new **HydroPower RO S** at low investment cost, cleaning with pure water can be achieved at minimal running cost – especially in hard water areas. Due to its compact and robust design, the new **HydroPower RO S** system is easy to transport.

The proven RO-technology from **UNGER** relies on a 3-stage filtration process with 0 ppm outgoing pure water, and the water is pressurized by a high-quality stainless steel pump.

The boost function allows a strong tap water-jet on demand for prewashing of heavy soiled or horizontal surfaces. It will also remove cobwebs and dirt from corners that cannot be reached with a brush.

Save money now and get your jobs done with the new **UNGER HydroPower RO S**.



BOOST MODE

- Pure water mode: for spotless cleaning of windows and facades
- Boost mode: tap water with 8-10 bar for prewashing of heavy-soiled surfaces

HIGH QUALITY 3-STAGE FILTRATION

1. Combi pre-filter to capture chlorine and sediments
2. Premium RO membrane to remove dissolved minerals
3. DI polisher to filter any remaining impurities = 100% pure water!

POWERFUL HIGH-VALUE PUMP

- Centrifugal pump for constant and high water flow
- Made of stainless steel
- Trouble-free operation even after long periods of non-use

EASY TO TRANSPORT

- Compact unit fits in the boot of a vehicle
- Easy to load, unload and manoeuvre
- Automatic water stop prevents leaking



HYDRO POWER[®] RO SYSTEM S

NEW!



EASY AND SAFE USAGE

- TDS meter displays the quality of the outgoing water at the touch of a button
- Manual flushing of RO membrane for an extended lifetime
- Automatic shut-off function for protection of the pump in case the water supply stops

EASY TO MAINTAIN

- Pre-filter and DI polisher are easy to change and can be visually controlled during work
- Removable back cover for easy access to all electric components

COMPACT AND ROBUST DESIGN

- Made of premium quality materials – long service life
- Durable stainless metal quick-release connectors, designed to eliminate leaks or drips
- Heavy duty stainless steel frame with maintenance free solid rubber wheels



HYDROPOWER[®] RO SYSTEM



S



M



L

	HydroPower[®] RO S (R020C)	HydroPower[®] RO M (R035C)	HydroPower[®] RO L (R040C)
Main features	<ul style="list-style-type: none"> • Compact design 	<ul style="list-style-type: none"> • High performance • Easy operation 	<ul style="list-style-type: none"> • Maximum performance • Digital assistance system • Automatic maintenance function
Water output* up to	180 l/h Boost mode: 1.000 l/h	350 l/h	400 l/h
Water outlets	1	2	3
Pump performance	0,6kW	0,6 kW	0,75 kW
Protection class electric pump	IP54	IP54	IP54
Inlet pressure [Bar]	1 – 6	1 – 6	1 – 6
Max. operating pressure [Bar]	10	10	10
Pump dry run protection	✓	✓	✓
Water flow meter	analog	analog	digital
Pre-filter	Combi filter Chlorine/Sediments (ROCA2)	Combi filter Chlorine/Sediments (ROCAR)	Combi filter Chlorine/Sediments (ROCAR)
Membranes	1 (ROME2)	2 (ROMEM)	2 (ROMEM)
Resin filter	Cartridge (RORE2)	Cartridge (RORES)	Cartridge (RORES)
TDS sensors	At water outlet	After membranes At water outlet	After pre-filter After membranes At water outlet
Dimensions in cm (height x width x depth)	96 x 53 x 67	107 x 53 x 70	107 x 53 x 70
Tare weight in kg	45	75	75
Weight incl. filling in kg	50	80	80
Cable length in m	1,5	1,5	1,5

* at 18°C water temperature and connected outlet hose with 1/2" inner diameter

UNGER Germany GmbH
Piepersberg 44
D-42653 Solingen
Germany
Tel.: (49) 212 2207 0
Fax: (49) 212 2207 222
ungereurope@ungerglobal.com

The general terms of delivery and payment of Unger Germany GmbH apply. Valid from 01.01.2021. With any orders placed by our commercial trade customers and with our deliveries. All data is without guarantee. Subject to alterations.

